



# DEEP RECESSED LED Spotlight 10W

DEEP RECESSED LED Spotlight is a proposal for customers who are looking for small luminaires characterized not only by top technical parameters, but also remarkable design. Lamp is available in many variants - resulting from the possibility of using different reflectors or housing colors. We can choose white or black housing, and reflectors: white, silver matte, silver glossy, copper matte, copper glossy, and black.

Fixtures are also available with three different beam angles: 24 °, 36 ° or 55 °.



Code*:	CCT/CRI:	Power LED/fixture:	Φ Fixture/LED:	Housing:
63-10-1xx1	4000K/90	10W/11W	800/1050lm	white
63-10-1xx2	4000K/90	10W/11W	800/1050lm	silver matte
63-10-1xx3	4000K/90	10W/11W	800/1050lm	silver glossy
63-10-1xx4	4000K/90	10W/11W	800/1050lm	copper matte
63-10-1xx5	4000K/90	10W/11W	800/1050lm	copper glossy
63-10-1xx9	4000K/90	10W/11W	800/1050lm	black
63-10-2xx1	3000K/90	10W/11W	750/1000lm	white
63-10-2xx2	3000K/90	10W/11W	750/1000lm	silver matte
63-10-2xx3	3000K/90	10W/11W	750/1000lm	silver glossy
63-10-2xx4	3000K/90	10W/11W	750/1000lm	copper matte
63-10-2xx5	3000K/90	10W/11W	750/1000lm	copper glossy
63-10-2xx9	3000K/90	10W/11W	750/1000lm	black

**Parameters:**  
 power factor (PF): >0,95  
 voltage: 230V AC (via external 250mA Philips CertaDrive driver)  
 beam angle: 24°, 36°, or 55°  
 light source: COB LED CREE  
 lifetime L70/B50/C10: 40.000 hours (according to IEC 62717 norm)  
 CRI: CRI90 (R9>50)  
 IP: IP44

**Dimensions:**  
 diameter: fi 89mm  
 height: 108mm  
 cut hole: fi 79mm

\*x (beam angle) 2-24°, 3-36°, 5-55° (eg. 63-10-1311 = 36°)  
 \*x (housing) 1-white, 9-black (eg. 63-10-1311 = white)

**Material:**  
 aluminium housing + PCV

**Additional picture:**

